



CMS390 Dual Joist Ceiling Plate

- Attaches to finished ceilings and provides lateral shift between joists
- Joist Width: 16" (406 mm)
- Weight Capacity: 500 lbs (227 kg)



CMS391 Dual Joist Ceiling Plate

- Attaches to finished ceilings and provides lateral shift between joists
- Joist Width: 24" (610 mm)
- Weight Capacity: 500 lbs (227 kg)



CMA395 Angled Ceiling Plate

- Adjustable for installation on angled ceilings
- Weight Capacity: 500 lbs (227 kg)
- Available in black and white




CMA106 Junction Box Assembly Ceiling Plate

- Designed for easy installation with any ceiling height
- Use any length of 1.5" NPT to achieve the appropriate extension
- Weight Capacity: 50 lbs (22.7 kg)
- Available in black




CEILING ADAPTERS

Common Installations



suspended
CMS440 & CMA470



suspended
CMS445

CMA440 Above-Tile Suspended Ceiling Kit

- Flexible solution supports column placement within 2' x 2' (600 x 600 mm) or 2' x 4' (600 x 1200 mm) ceiling tile
- Includes 10' (3 m) safety cable, 20' (6.1 m) strand wire, four turnbuckles, wood eye bolts, concrete anchors and a chrome finishing ring
- Weight Capacity: 50 lbs (22.7 kg)



CMS440 Above-Tile Suspended Ceiling Kit

- Flexible solution provides infinite column placement within 2' x 2' (600 x 600 mm) or 2 x 4' (600 x 1200 mm) ceiling tile
- WireVice™ cable suspension system for quick and easy tie-off (includes four 25' [7.62 m] cables)
- TwisTile™ ceiling tile cutter easily pierces circular hole for column
- Weight Capacity: 50 lbs (22.7 kg)



CMS440P Suspended Ceiling Kit with Power Conditioner

- Combines CMS440 with PX2W high-performance power conditioning outlet
- Protects equipment, cleans signal and speeds installation in pre-assembled package
- Weight Capacity: 50 lbs (22.7 kg)





CEILING ADAPTERS cont.

CMA450 Heavy-Duty, Above-Tile Suspended Ceiling Kit

- Heavy-duty solution supports center, side and corner positions within a 2' x 2' (600 x 600 mm) ceiling tile
- Includes 10' (3 m) safety cable, 20' (6.1 m) strand wire, four turnbuckles, wood eye bolts, concrete anchors and a chrome finishing ring
- Weight Capacity: 250 lbs (113.6 kg) center hole, 125 lbs (56.8 kg) side and corner holes




CMS445 Suspended Ceiling Tile Replacement Kit

- Future-proofs installations by providing post-installation adjustments
- Provides infinite column placement within a 2 x 2' (600 x 600 mm) ceiling tile
- WireVice cable suspension system for quick and easy tie-off (includes four 25' [7.62 m] cables)
- Weight Capacity: 50 lbs (22.7 kg)



CMS445P Suspended Ceiling Tile Replacement Kit with Power Conditioner

- Combines CMS445 with PX2W high-performance power conditioning outlet
- Protects equipment, cleans signal and speeds installation in pre-assembled package
- Weight Capacity: 50 lbs (22.7 kg)



CMA455 Heavy-Duty Suspended Ceiling Tile Replacement Kit

- Heavy-duty solution supports center column placement within a 2' x 2' (600 x 600 mm) ceiling tile
- Includes 10' (3 m) safety cable, 20' (6.1 m) strand wire, four turnbuckles, wood eye bolts, concrete anchors and a chrome finishing ring
- Weight Capacity: 250 lbs (113.6 kg)



CMA470 Above-Tile Storage Accessory

- Provides storage for equipment above the suspended ceiling
- Hinged door for easy access
- Compatible with CMS440, CMA440, CMA450 and CMA455 ceiling kits



CMA471 Above-Tile Large Storage Accessory

- Provides storage for larger equipment above the suspended ceiling
- Hinged door for easy access
- Compatible with CMS440, CMA440, CMA450 and CMA455 ceiling kits



CMA472 Above-Tile Storage Accessory

- Provides storage for larger equipment above the suspended ceiling
- Supports wide, thin equipment in a horizontal orientation
- Compatible with CMS440 and CMA440 ceiling kits



CMSZ006 0-6" Fully Threaded Column

- Provides infinite height adjustment from suspended ceiling kits
- Compatible with all Chief suspended ceiling kits
- Available in black and silver



POWER ACCESSORIES

PX2W Power Conditioner Outlet

- Wall or ceiling mounted outlet with integrated power conditioning
- Filter removes more noise than many full-sized line conditioners
- Non-volatile spike protection with LED protection indicator can potentially absorb thousands of spikes
- Non-current limiting design passes full power on a regular circuit
- Picture and sound available after protection stops until a replacement can be installed
- Rated for 2160 joules and 15 amps





STRUCTURAL ADAPTERS

Common Installations



truss
CMA365 & CMA366



unistrut
CMA372 & CMA110

CMA300 Pole Clamp

- Clamps to horizontal poles and transitions to vertical extension column
- Pole Outside Diameter(s): 1.9-3.5" (48-89 mm)
- Weight Capacity: 300 lbs (136.4 kg)



CMA360 I-Beam Clamp

- Clamps to I-beams and transitions to vertical extension column
- Weight Capacity: 250 lbs (113.4 kg)



CMA362 C Clamp

- Universal clamp for a variety of structures and transitions to vertical extension column
- Clamp Range: up to 2.75" (70 mm) O.D. (including wood 2 x 4")
- Weight Capacity: 250 lbs (113.6 kg)



CMA365 Truss Ceiling Adapter

- Universal clamp for square, round, rectangular or I-beam truss
- Clamp Range: 0.75-3" (19-76 mm) O.D.
- Weight Capacity: 250 lbs (113.6 kg)



CMA366 Architectural Spanning Adapter

- Spans truss systems and provides lateral shift capability
- Span Distance: 5-18" (127-457 mm)
- Clamp Range: up to 2" (51 mm) O.D. or 1.9" (48 mm) square tubing
- Weight Capacity: 250 lbs (113.6 kg)



CMA372 Offset Unistrut Adapter

- Features offset for transitioning cables out of extension columns
- Includes spring nuts and bolts to attach to 1.63" (41 mm) unistrut
- Weight Capacity: 500 lbs (227 kg)



CMA165 Internal Joist Ceiling Kit

- Expands to bridge ceiling joists and transition to vertical extension column
- Joist Width: 16 or 24" (406 or 610 mm)
- Weight Capacity: 50 lbs (22.7 kg)



CMA385 Internal Joist Mount

- Expands to bridge ceiling joists and transition to vertical extension column
- Joist Width: 10-23" (254-584 mm)
- Weight Capacity: 300 lbs (136 kg)



WMA1S Wall Mount Arm Accessory

- Fast installation with innovative quick-connect system
- Micro leveling adjustment
- Integrated cable management system conceals and protects cables
- Compatible with CMS extension columns up to 4' (1.2 m) (not included)
- Includes hardware for wood stud, steel stud, and concrete wall construction





EXTENSION COLUMNS

Common Installations



fixed & adjustable

CMS0XX Fixed Extension Columns

- Aluminum extension columns feature easy installation and maximum strength
- Flow-through cable management with cable exit port (9" [229 mm] or longer)
- Weight Capacity: 500 lbs (227 kg)
- Available in black, silver and white



Model	Length
CMS003*	3" (76 mm)
CMS006*	6" (152 mm)
CMS009	9" (229 mm)
CMS012	12" (305 mm)
CMS018	18" (457 mm)

Model	Length
CMS024	2' (0.6 m)
CMS036	3' (0.9 m)
CMS048	4' (1.2 m)
CMS060	5' (1.5 m)
CMS072	6' (1.8 m)

* Steel construction.

CMS0XX0XX Adjustable Extension Columns

- Aluminum extension columns feature notched design for adjustment without disassembly
- Flow-through cable management with cable exit port (12" [305 mm] or longer)
- Weight Capacity: 500 lbs (227 kg)
- Available in black, silver and white



Model	Length	Model	Length
CMS006009	6-9" (152-229 mm)	CMS0406	4-6' (1.2-1.8 m)
CMS009012	9-12" (229-305 mm)	CMS0507	5-7' (1.5-2.1 m)
CMS012018	12-18" (305-457 mm)	CMS0608	6-8' (1.8-2.4 m)
CMS018024	18-24" (457-610 mm)	CMS0709	7-9' (2.1-2.7 m)
CMS0203	2-3' (0.6-0.9 m)	CMS0810	8-10' (2.4-3.1 m)
CMS0305	3-5' (0.9-1.5 m)	CMS0911	9-11' (2.7-3.4 m)
		CMS1012*	10-12' (3.1-3.7 m)

* Cannot ship by UPS due to length.

COLUMN ACCESSORIES

Common Installations



cable management
CMA274



stability
CMA340

CMA274 Cable Cover for Columns

- Snap-on cover for routing cables alongside extension columns
- Hides cables for a clean appearance
- CMA275: Kit of three CMA274



CMA340 Stabilization Kit for Columns

- Cable system attaches to extension column for increased rigidity
- Includes one pole clamp, four cables and four turnbuckles
- Weight Capacity: 500 lbs (227 kg)



CMA640 Decorative Ring for Columns

- Conceals pass-through hole cut in ceiling structure for extension column
- Hinged design for new or retrofit installations
- Clamp Range: 1.9" (48 mm) O.D. (fits CMS fixed and CMS adjustable inner column only)
- Available in black, chrome and white



CMA643 Decorative Ring for Columns

- Conceals pass-through hole cut in ceiling structure for outer adjustable extension column
- Clamp Range: 2.44" (62 mm) O.D. (fits CMS adjustable outer column only)
- Available in chrome





COLUMN ACCESSORIES cont.

CMA170 Storage Accessory

- Clamps on to columns for storage of electronic components
- Mounts horizontally or vertically
- Weight Capacity: 25 lbs (11.3 kg)



CMA480 Column Storage Shelf

- Supports wide, thin AV equipment in a horizontal orientation
- Flush-to-ceiling installation possible with doors to access equipment
- Compatible with CMS fixed and adjustable extension columns
- Weight Capacity: 25 lbs (11.3 kg)



CMS261 Column Cut-Off Adapter

- Adds 1-1/2" NPT threads to column that has been cut to length
- Adds 2" (51 mm) of height to installation
- Weight Capacity: 500 lbs (226.8 kg)



IN-LINE COLUMN ADAPTERS

Common Installations



vibration
CMA347



electrical
CMA504

CMA270 Coupler

- Connects two extension columns for extended length applications
- Weight Capacity: 500 lbs (227 kg)
- Available in black, silver and white



CMA152 Coupler with Cable Port

- Connects two extension columns and integrates a cable exit port
- Weight Capacity: 500 lbs (227 kg)



CMA351 Coupler with Swivel

- Connects two extension columns with swivel capability
- Swivel Range: 0-330° (with limited adjustment)
- Weight Capacity: 500 lbs (227 kg)



CMA160 Installation Job Box Coupler

- Connects two extension columns with storage space for electronic equipment
- Features outlet knockouts and plenum rating
- Weight Capacity: 250 lbs (113.6 kg)





IN-LINE COLUMN ADAPTERS cont.

CMA347 Vibration Isolating Coupler

- Connects two extension columns and isolates vibration transmitted to lower column
- Patented design isolates vibration to reduce image movement
- Weight Capacity: 0-15 lbs (0-6.8 kg) or 15-35 lbs (6.8-15.9 kg)



CMA151 Adapter/Reducer

- Adapts 1-1/2" NPT coupler to 1" NPT column
- Weight Capacity: 250 lbs (113.6 kg)



CMA251 Adapter/Reducer

- Adapts 2" NPT coupler to 1-1/2" NPT column
- Weight Capacity: 500 lbs (227 kg)



CMA278 Vinyl End Cap

- Covers the end of extension column for clean appearance
- Pre-cut for routing cables through cover
- Ten caps per kit

CMA273 End Cap


- Covers the end of extension column for clean appearance

CMA502 Electrical Outlet Coupler

- Connects two extension columns and supports one electrical outlet
- Weight Capacity: 500 lbs (227 kg)
- 1-1/2" NPT
- Black

CMA504 Electrical Outlet Coupler

- Connects two extension columns and supports two electrical outlets
- Weight Capacity: 500 lbs (227 kg)
- 1-1/2" NPT
- Black



OTHER INSTALLATION ACCESSORIES

LSB100 RPA Projector Lateral Shift Bracket

- Allows lateral shift of projector when used with RPA or RPM mounts
- Maintains quick disconnect feature and includes All-Points Security
- Shift Range: 0-3" (0-76 mm) or 3-5.25" (76-133 mm)
- Weight Capacity: 50 lbs (22.7 kg) at 0-3" or 15 lbs (6.8 kg) at 3-5.25"



LSB101 RPM with Q-Lock Projector Lateral Shift Bracket

- Allows lateral shift of projector when used with RPM mounts
- Maintains quick disconnect feature and includes All-Points Security
- Shift Range: 0-3" (0-76 mm)
- Weight Capacity: 50 lbs (22.7 kg)



TMA100 Projector Tripod Mount

- Converts a standard tripod into a projector stand
- Connects SLB custom or universal interfaces (not included)
- Weight Capacity: 25 lbs (11.3 kg)



CMA250 LCDA Flush Mount Adapter

- Adds flush mount capability to an LCDA projector mount

LPK1 VCM Flush Mount Adapter

- Adds flush mount capability to an VCM projector mount

CMA290 Wire Suspension Locks

- Combine with flexible wire rope to hang various equipment
- One-way clamp mechanism and quick-release lever for ease of installation
- Ten clamps per kit





SECURITY

Common Installations



classroom
PG2A

PG1A Large Projector Guard

- Fully encloses projector in locked cage to prevent theft or damage
- Adjustable front opening to accommodate different lens positions
- Hinged door for easy access
- Projector Sizes (HxWxD):
RPA - 20.4 x 7.5 x 20"
(518 x 190 x 508 mm),
RPM - 20.4 x 6.5 x 20"
(518 x 165 x 508 mm)
- Available in black and white



PG2A Small Projector Guard

- Fully encloses projector in locked cage to prevent theft or damage
- Adjustable front opening to accommodate different lens positions
- Hinged door for easy access
- Projector Sizes (HxWxD):
RPA - 16 x 7.5 x 16"
(406 x 190 x 406 mm),
RPM - 16 x 6.5 x 16"
(406 x 165 x 406 mm)
- Available in black and white



PG3A Extra Large Projector Guard

- Fully encloses projector in locked cage to prevent theft or damage
- Adjustable front opening to accommodate different lens positions
- Hinged door for easy access
- Projector Sizes (HxWxD):
RPA - 10.75 x 25.0 x 25.0"
(273 x 635 x 635 mm),
RPM - 14.33 x 25.24 x 25.51"
(364 x 641 x 648 mm)
- Available in black and white



PL1 RPA Large Projector Lock

- Conceals projector connection points and adds keyed locking to RPA installations
- Three unique locks available (PL1A, PL1B, and PL1C)



PL2 RPA Small Projector Lock

- Adds keyed locking to RPA installations
- Three unique locks available (PL2A, PL2B, and PL2C)



HC1 Heavy-Duty Cable System

- Security cable system with adhesive pads and SA1 security anchor
- Includes security anchor, vinyl-coated cable, 40 mm padlock, two security pads with rotating cable fasteners, and a tube of instant adhesive



SA1 Security Anchor

- Provides secure anchor point to 1-1/2" NPT pipe, truss or other structure
- Security shroud held in position by cable or padlock (not included)



LC1 Cable System

- Security cable system with adhesive pads for securing sensitive equipment
- Includes 6' (1.8 m) coiled cable, two steel security pads, instant adhesive and a 30 mm padlock



PL4 Cable Lock

- Security cable system with 3M adhesive-backed steel pad for securing sensitive equipment
- Seamless lock housing with a seven-pin tumbler locking mechanism (two keys provided)





SECURITY cont.


SSC Secure Screw Cover Kits

- Prohibit access to equipment mounting screws with cable or padlock (not included)
- SSC1: 3 covers up to #10 (M5), SSC2: 3 covers for screws up to 0.25" (M6), SSC3: 3 covers for screws up to 0.31" (M8), SSC4: for RPA projector mounts



PMSC Security Cable Lock

- Use with security projector mounts to deter theft attempts by tearing out projector inserts
- One-way clamp mechanism and quick-release lever for ease of installation
- Includes two locks and two cables with protective tubing



SEC2 Security Cable Kit for New SLBU

- Use with RPA series or RPA Elite® series mounts with new SLBU for additional security
- One-way clamp mechanism and quick-release lever for ease of installation
- Includes two locks and two cables



PROJECTOR STACKERS

LCD2C Dual Projector Ceiling Stacker

- Ceiling mount accessory for two vertically-stacked projectors
- Requires two RPA or RPM projector mounts
- Projector Width: 18" (457 mm)
- Weight Capacity: 100 lbs (45.5 kg)



LCD2TS Dual Projector Table Stand Stacker

- Table stand accessory for two vertically-stacked projectors
- Requires two RPA or RPM projector mounts
- Projector Width: 18" (457 mm)
- Weight Capacity: 100 lbs (45.5 kg)



LCDB Stacker Base

- Use with extension columns to create custom table stand projector stacker system
- Max Column Length: 3' (0.9 m)
- Weight Capacity: 100 lbs (45.5 kg)



LCDPA Stacker Arm

- Use with extension columns to create custom projector stacker system
- Attaches to RPA or RPM projector mounts
- Weight Capacity: 50 lbs (22.7 kg)

LCDCP Stacker Ceiling Plate

- Use with extension columns to create custom table stand projector stacker system
- Max Column Length: 6' (1.8 m)
- Weight Capacity: 100 lbs (45.5 kg)



PROJECTOR KITS

Common Installations



KITES003

KITES003 Projector Suspended Ceiling Kit

- Includes RPMU, CMS003, CMS440

KITES003P Projector Suspended Ceiling Kit

- Includes RPMU, CMS003, CMS440, CMA470

KITLS003 Projector Suspended Ceiling Kit

- Includes RPMA1, CMS003, CMS440

KITPS003 Projector Suspended Ceiling Kit

- Includes RPAU, CMS003, CMS440

KITPA018024 Projector Angled Ceiling Kit

- Includes RPAU, CMS018024, CMA395

KITPD0203 Projector Flat Ceiling Kit

- Includes RPAU, CMS0203, CMS115

