

## WHAT YOU NEED TO KNOW

### **ABOUT RPMA1**

- Industry-first micro-adjustable projector mount
- Keyed locking options (A/B/C/D)
- No tamper resistant hardware required
- Universal interface and also supports optional custom SLBs
- Compatible with a wide array of accessories

## **FEATURES**

MICROZONE™ ADJUSTMENTS PATENT-PENDING

This feature makes projector registration fast and precise (including flush-mount installations).

2 CENTRIS® TECHNOLOGY

PATENT-PENDING

Enables effortless fingertip positioning. Selfadjusts to support different projector weights.

QUICK CONNECT/DISCONNECT
Convenient lamp and filter access on most
projectors. Disconnecting maintains registration
and doesn't affect pre-set adjustments.

4 CABLE MANAGEMENT
Route cables through top of mount without additional accessories.

5 COMPLETE SECURITY
Universal mounting interface with secured mounting points for high-risk environments.

# SPECIFICATIONS Roll ±3° Pitch ±20° Yaw 360° Dimensions 3.8" x 14.6" x 12.3" (97 x 371 x 312 mm) Color Black, White Weight Capacity 50 lbs (22.7 kg)

# RECOMMENDED ACCESSORIES



CMS SUSPENDED CEILING KITS



**CMS EXTENSION COLUMNS** 



**PMSC** Security Cables

For a complete list of projector mount accessories see page 21.

## TECHNICAL DRAWINGS





