

INSTALLATION INSTRUCTIONS



Economy Rack Door

DISCLAIMER

Milestone AV Technologies and its affiliated corporations and subsidiaries (collectively "Milestone"), intend to make this manual accurate and complete. However, Milestone makes no claim that the information contained herein covers all details, conditions or variations, nor does it provide for every possible contingency in connection with the installation or use of this product. The information contained in this document is subject to change without notice or obligation of any kind. Milestone makes no representation of warranty, expressed or implied, regarding the information contained herein. Milestone assumes no responsibility for accuracy, completeness or sufficiency of the information contained in this document.

Chief® is a registered trademark of Milestone AV Technologies. All rights reserved.



IMPORTANT SAFETY INSTRUCTIONS!



WARNING: A WARNING alerts you to the possibility of serious injury or death if you do not follow the instructions.



CAUTION: A CAUTION alerts you to the possibility of damage or destruction of equipment if you do not follow the corresponding instructions.



WARNING: Failure to read, thoroughly understand, and follow all instructions can result in serious personal injury, damage to equipment, or voiding of factory warranty! It is the installer's responsibility to make sure all components are properly assembled and installed using the instructions provided.



WARNING: Use this mounting system only for its intended use as described in these instructions. Do not use attachments not recommended by the manufacturer.



WARNING: Never operate this mounting system if it is damaged. Return the mounting system to a service center for examination and repair.





WARNING: Do not use this product outdoors.


IMPORTANT ! : Minimum spacings between the Accessories and components and the (ITC/AV) Rack Enclosure shall be maintained for safe operation of the equipment when installed in accordance with the National Electric Code, ANSI/NFPA 70-2008. Operating temperature inside rack shall not exceed 104° F.

--SAVE THESE INSTRUCTIONS--


LEGEND

	<p>Tighten Fastener</p> <p>Apretar elemento de fijación</p> <p>Befestigungsteil festziehen</p> <p>Apertar fixador</p> <p>Serrare il fissaggio</p> <p>Bevestiging vastdraaien</p> <p>Serrez les fixations</p>		<p>Pencil Mark</p> <p>Marcar con lápiz</p> <p>Stiftmarkierung</p> <p>Marcar com lápis</p> <p>Segno a matita</p> <p>Potloodmerkten</p> <p>Marquage au crayon</p>
	<p>Loosen Fastener</p> <p>Aflojar elemento de fijación</p> <p>Befestigungsteil lösen</p> <p>Desapertar fixador</p> <p>Allentare il fissaggio</p> <p>Bevestiging losdraaien</p> <p>Desserrez les fixations</p>		<p>Drill Hole</p> <p>Perforar</p> <p>Bohrloch</p> <p>Fazer furo</p> <p>Praticare un foro</p> <p>Gat boren</p> <p>Percez un trou</p>
	<p>Phillips Screwdriver</p> <p>Destornillador Phillips</p> <p>Kreuzschlitzschraubendreher</p> <p>Chave de fendas Phillips</p> <p>Cacciavite a stella</p> <p>Kruiskopschroevendraaier</p> <p>Tournevis à pointe cruciforme</p>		<p>Adjust</p> <p>Ajustar</p> <p>Einstellen</p> <p>Ajustar</p> <p>Regolare</p> <p>Afstellen</p> <p>Ajuster</p>
	<p>Open-Ended Wrench</p> <p>Llave de boca</p> <p>Gabelschlüssel</p> <p>Chave de bocas</p> <p>Chiave a punte aperte</p> <p>Steeksleutel</p> <p>Clé à fourche</p>		<p>Remove</p> <p>Quitar</p> <p>Entfernen</p> <p>Remover</p> <p>Rimuovere</p> <p>Verwijderen</p> <p>Retirez</p>
	<p>By Hand</p> <p>A mano</p> <p>Von Hand</p> <p>Com a mão</p> <p>A mano</p> <p>Met de hand</p> <p>À la main</p>		<p>Optional</p> <p>Opcional</p> <p>Optional</p> <p>Opcional</p> <p>Opzionale</p> <p>Optie</p> <p>En option</p>
	<p>Hex-Head Wrench</p> <p>Llave de cabeza hexagonal</p> <p>Sechskantschlüssel</p> <p>Chave de cabeça sextavada</p> <p>Chiave esagonale</p> <p>Zeskantsleutel</p> <p>Clé à tête hexagonale</p>		<p>Security Wrench</p> <p>Llave de seguridad</p> <p>Sicherheitsschlüssel</p> <p>Chave de segurança</p> <p>Chiave di sicurezza</p> <p>Veiligheidsleutel</p> <p>Clé de sécurité</p>

TOOLS REQUIRED FOR INSTALLATION



PARTS



DIMENSIONS

MODEL NUMBER	DESCRIPTION	DIMENSION "A"
ERD-8	ECONOMY RACK PLEXI DOOR-8 SPACES	15.75 [400.0mm]
ERD-12	ECONOMY RACK PLEXI DOOR-12 SPACES	22.75 [577.9mm]
ERD-16	ECONOMY RACK PLEX DOOR-16 SPACES	29.75 [755.6mm]
ERD-20	ECONOMY RACK PLEX DOOR-20 SPACES	36.75 [933.5mm]
ERD-8P	ECONOMY RACK PERF DOOR-8 SPACES	15.75 [400.0mm]
ERD-12P	ECONOMY RACK PERF DOOR-12 SPACES	22.75 [577.9mm]
ERD-16P	ECONOMY RACK PERF DOOR-16 SPACES	29.75 [755.6mm]
ERD-20P	ECONOMY RACK PERF DOOR-20 SPACES	36.75 [933.5mm]

ERD-16 SHOWN

ASSEMBLY

IMPORTANT ! : The following installation instructions assume the ER rack has already been completely assembled. Complete ER rack assembly following ER rack installation instructions prior to installing the ERD door.

IMPORTANT ! : The ERD doors were designed specifically to be installed to the front of the ER racks. Do NOT attempt to install this door to any other rack or mounting device.

NOTE: The hinge member that attaches to the front edge of the rack is the same width and height as the rack and should be lined up as such.

1. Measure and mark 1" from the top and bottom of the edge on what will be the hinge side of the door. (See Figure 1)

NOTE: Door can be connected on either side depending on user preference.

2. Drill a 1/16" hole, 1/2" in depth, at each of these marked locations. (See Figure 1)
3. Use two #10 x 5/8" Phillips pan wood screws (D) to attach door (A) at drilled hole locations. (See Figure 1)




Figure 1

4. Drill 1/16" holes, 1/2" in depth, at remaining hole locations. (See Figure 2)
5. Install one #10 x 5/8" Phillips pan wood screw (D) in each drilled hole location to fully secure door (A) to rack. (See Figure 2)
6. Install four nail glides (B) on underside of rack in order to allow door to swing freely above ground. (See Figure 2)
7. Close door (A). (See Figure 2)




Figure 2

8. With door closed, turn the lock so that the "cam" ("L" shaped part of lock) is horizontal.
9. Position lock bracket (C) over cam making sure the cam can clear the bracket when turned completely from locked to unlocked position.
10. Mark the location of the two holes on the lock bracket (C). (See Figure 3)
11. Drill two 1/16" holes, 1/2" in depth, at these marked locations. (See Figure 3)
12. Use two #10 x 5/8" Phillips pan wood screws (D) to attach lock bracket (C) to rack. (See Figure 3)




Figure 3

13. Install one of four spacers (E1-E4) into hole on cam to provide the desired spacing between cam and lock bracket. (See Figure 4)




Figure 4

NOTE: Only clean the door with water, mild detergent and a soft cloth.



Our Mounts. **Your Vision.**

Chief Manufacturing, a products division
of Milestone AV Technologies

8800-002279 Rev00
©2013 Milestone AV Technologies, a
Duchossois Group Company
www.chiefmfg.com
01/13

USA/International	A 6436 City West Parkway, Eden Prairie, MN 55344 P 800.582.6480 / 952.225.6000 F 877.894.6918 / 952.894.6918
Europe	A Franklinstraat 14, 6003 DK Weert, Netherlands P +31 (0) 495 580 852 F +31 (0) 495 580 845
Asia Pacific	A Office No. 1 on 12/F, Shatin Galleria 18-24 Shan Mei Street Fotan, Shatin, Hong Kong P 852 2145 4099 F 852 2145 4477

