

---

# INSTALLATION INSTRUCTIONS


---

## Chief GSU Large Screen Display Mount

The Chief GSU Large Screen Display Mount is a quick disconnect mounting solution for large flat panel displays. The mount self-adjusts for the weight of different display screens.

Once the brackets are attached to your display, simply mount the GSU securely on a wall, lock the display in place and attach your audio/video cables.

**! IMPORTANT:** If the installation of this product requires OSHPD seismic approval, refer to OSHPD pre-approval documents and drawings before beginning installation. OSHPD documents and drawings are available at [www.chiefmfg.com](http://www.chiefmfg.com), and located on the product information page for the mount.



### BEFORE YOU BEGIN

---

- **Caution:** To prevent damage to the mount, which could void factory warranty and affect the attached equipment, thoroughly study all instructions and illustrations before you begin the installation. Pay particular attention to the “Important Warnings and Precautions” on Page 1.
- The mount is designed to be installed using wall studs or supporting framework. The fasteners used to anchor the mount must be capable of supporting five times the total weight of the equipment.
- The maximum weight to be installed on the GSU mount is 175 pounds (79.38 Kg).
- If you have any questions about this installation, contact Chief Manufacturing at 1-800-582-6480.



## IMPORTANT WARNINGS AND PRECAUTIONS!

- WARNING:** A **WARNING** alerts you to the possibility of serious injury or death if you do not follow the instructions.
- CAUTION:** A **CAUTION** alerts you to the possibility of damage or destruction of equipment if you do not follow the corresponding instructions.
- **WARNING: Improper installation can result in serious personal injury! Make sure that the structural members can support a weight factor *five times* the total weight of the equipment. If not, reinforce the structure before installing the mount.**
  - **WARNING: Be aware also of the potential for personal injury or damage to the unit if it is not adequately mounted.**
  - **WARNING: The installer is responsible for verifying that the structure to which the mount is anchored will safely support four times the combined load of all attached components or other equipment.**
  - **WARNING: The weight of the display placed on the GSU must not exceed 175 lbs. (79.38 kg), the maximum load capacity of the GSU.**
  - **WARNING: Watch for pinch points. Do not put your fingers between movable parts.**
  - **WARNING: Make sure the mount and brackets are correctly oriented.**
  - **CAUTION:** Check the unit for shipping damage before you begin the installation.
  - **CAUTION:** Use only the mounting screws provided and **DO NOT OVER TIGHTEN** mounting screws.

## CONTENTS

TOOLS REQUIRED FOR ASSEMBLY .....	2
PARTS .....	2
INSPECT THE MOUNT BEFORE ASSEMBLY .....	4
INSTALL INTERFACE BRACKETS ON DISPLAY .....	4
INSTALL WALL PLATE.....	6
INSTALL DISPLAY.....	7

## TOOLS REQUIRED FOR INSTALLATION

- Phillips screwdrivers, No. 1 and No. 2 TIP
- Drill and bit set
- Wrench set

**NOTE:** Other tools may be required depending on the method of installation.

## PARTS

**Table 1: Parts**

Ref	Description	Qty	Ref	Description	Qty
10	PLATE, Wall with two latches attached	1	130	SCREW, Phillips, M4 x 20 (Parts Bag D)	8
20	BRACKET, Interface	2	140	SCREW, Phillips, M4 x 25 (Parts Bag D)	8
30	HOOK, Static	2	150	WASHER, Flat, #10 (Parts Bag E)	8
40	SCREW, Phillips, M8 x 20 (Parts Bag A)	6	160	WASHER, Flat, 1/4" (Parts Bag F)	8
50	SCREW, Phillips, M8 x 30 (Parts Bag A)	6	170	SPACER, 1/4" (Parts Bag G)	8
60	SCREW, Phillips, M8 x 45 (Parts Bag A)	6	180	SPACER, 1/2" (Parts Bag G)	8
70	SCREW, Phillips, M6 x 25 (Parts Bag B)	8	190	WASHER, Shoulder, .195"ID (Parts Bag E)	8
80	SCREW, Phillips, M6 x 16 (Parts Bag B)	8	200	WASHER, Shoulder, .320"ID (Parts Bag F)	8
90	SCREW, Phillips, M5 x 16 (Parts Bag C)	8	210	SCREW, Self-Tapping (not shown)	2
100	SCREW, Phillips, M5 x 20 (Parts Bag C)	8	220	BOLT, Carriage, 1/4-20 x 1/2" (not shown)	6
110	SCREW, Phillips, M5 x 25 (Parts Bag C)	8	230	NUT, Nylock, 1/4-20 (not shown)	6
120	SCREW, Phillips, M4 x 16 (Parts Bag D)	8			




Figure 1. Parts

### INSPECT THE MOUNT BEFORE ASSEMBLY

1. Carefully inspect the mount for shipping damage (see Figure 1). If any damage is apparent, call your carrier claims agent and do not continue with the installation until the carrier has reviewed the damage.

**NOTE:** Read all assembly instructions before starting assembly.

2. Carefully inspect mount components for damage.

### INSTALL INTERFACE BRACKETS ON DISPLAY

Install the interface brackets as follows:

1. Place the interface brackets (20) on the back of the display, aligning one of the holes or top of the slots as a reference point to align horizontally with the square holes facing toward the center of the display (see Figure 2 and Figure 3). Spacers (170 or 180) are provided for use with recessed mounting holes or protrusions on the back of the display that prevent the bracket from laying flat on the back of the display.
2. Using spacers (170 or 180), Nylon shoulder washers (190) to electrically isolate the mount from the display, appropriate M6 or M8 screws (40, 50, 60, 70 or 80), steel washers (200) as necessary, appropriate M4 or M5 screws (90, 100, 110, 120, 130 or 140) secure the brackets (20) to the display.




Figure 2. Place Brackets on Display




Figure 4. Attachment Parts




Figure 3. Align Holes




Figure 5. Attachment

3. Find the center line of the display (see Figure 6).
4. Attach brackets (20) with the center hole of the bracket assembly as close to the center line of the display as possible (see Figure 7), positioning the assembly with the knob side toward the outside of the display.




Figure 6. Center Line of Display




Figure 7. Attach Tilt Brackets

## INSTALL WALL PLATE

Install the wall plate as follows:

**WARNING: It is the responsibility of the installer to verify that the structure to which the mount is anchored will safely support four times the combined load of all attached components and equipment.**

1. Determine suitable a mounting location and lift the wall plate (10) into place (see Figure 8).
2. Using a small nail or screw (not provided) in the center hole, lightly hold wall plate at the mounting location (see Figure 9).
3. Level the wall plate (10) and drill pilot holes for anchoring the wall plate.
4. Using appropriate hardware (not included) for your installation, install the wall plate on the wall.
5. Slide the latches to the outside (see Figure 10).




Figure 8. Wall Plate Dimensions

CENTER HOLE TO FACILITATE LEVELING PROCESS OF WALL BRACKET




Figure 9. Wall Plate Installation

SLIDE LATCHES TO THE OUTSIDE PRIOR TO PLACING SCREEN ON BRACKET




Figure 10. Slide Latches Outward

## INSTALL DISPLAY

Install the display as follows:

1. Place the display on the wall plate (10) by hooking the hooks (30) of brackets (20) in the top of the wall plate (see Figure 11 and Figure 12).
2. Secure the display by sliding the latches, one on each side, inward (see Figure 13).
3. If desired, install self tapping screws and/or padlocks (not provided) for additional security (see Figure 14).




Figure 11. Hooks On Top (View 1)




Figure 12. Hooks On Top (View 2)




Figure 13. Slide Latches In




Figure 14. Added Security