



HB06E
VIDEO PROJECTOR CEILING MOUNT
FOR EIKI LC-SX6, LC-X6, CHRISTIE LS+58, LX66
SANYO PLC-EF60, PLC-XF60,

The Chief HB06E custom video projector ceiling mount is designed to provide fast, simple and secure installation. Special roll, pitch, yaw and horizontal adjustments simplify projection positioning for image alignment. The HB06E mount also has positive registration lock so the projector may be removed without losing projector mount registration.

WARNING: IMPROPER INSTALLATION MAY RESULT IN SERIOUS PERSONAL INJURY! All components must be securely fastened to each other and to the ceiling, **AND** the ceiling **MUST** be capable of supporting 5 times the total weight of the installation. If it cannot, the ceiling **MUST** be reinforced.

Unpack and check contents:

- | | | | |
|-----|-------------------------------------------|-----|---------------------------------|
| (1) | Deluxe ceiling mount housing assembly. | (7) | M8 Flat washers |
| (1) | Custom mounting bracket | (6) | M8 X 30mm button head cap screw |
| (4) | 5/16" flange nuts | (1) | M8 X 12mm button head cap screw |
| (6) | Nylon Spacers .680"OD X .390"ID X .625"TL | (1) | M5 Hex Key |

INSTALLATION INSTRUCTIONS

1. Turn your projector upside down.
2. Place the six nylon spacers over the six outer threaded inserts, to bring them flush with the bottom of the projector.
3. Place the custom mounting bracket on the projector so all seven holes in the custom bracket align with the seven mounting inserts in the bottom of the projector.
4. Place (1) M8 flat washer over the M8 X 12mm screw and start it in the front center mounting hole by hand. Place (1) M8 flat washer on each of the remaining (6) M8 X 30mm screws and start them all by hand, once they are all installed secure them using the hex key wrench provided. **Using the proper wrench securely tighten all seven mounting screws at this time.**
5. Be sure that the method of support you are using for the VCM ceiling mount is securely installed to the ceiling. If not, the ceiling must be reinforced. Improper installation may result in serious personal injury.
6. Attach the VCM housing to your method of support and tighten firmly so the VCM housing is square to the screen.

PRECAUTION: *Installing a ceiling mount requires the presence of two persons familiar with mechanical installations. A third assistant is recommended.*

7. With the help of your assistants, lift the projector and install it to the studs extending from the mounting plate. Be sure the custom mounting plate is seated in slots. **Tighten securely** using the (4) 5/16" flange nuts.

For projector alignment see attached sheet.

8803-000083