

LCD-7000CI CEILING MOUNT FOR EIKI LC 7000, SANYO PLS 5500

The Chief LCD-7000CI Ceiling Mount is designed for the EIKI LC 7000 / Sanyo PLS 5500 projector. The LCD-7000CI can be attached with standard NPT 1½” pipe column or with Chief’s CMA-100, Adjustable Column & Ceiling Plate or CMA-110, Flat Ceiling Plate.

Unpack carton and check contents:

(1)	LCD-7000 Plate	(1)	LCD-7000CI U-Form
(1)	LCD-7000 Top Cross Assembly	(3)	M5 x 16mm Bolts
(1)	⁵ / ₃₂ ” Allen Wrench	(3)	M5 Flatwashers
(1)	³ / ₁₆ ” Allen Wrench	(2)	#10 Flatwashers
(2)	10-24 Nylock Nuts	(4)	¼-20 Nylock Nuts
		(1)	⁵ / ₁₆ -18 Set Screw

WARNING: IMPROPER INSTALLATION MAY RESULT IN SERIOUS PERSONAL INJURY! All components must be securely fastened to each other and to the ceiling, **AND** the ceiling **MUST** be capable of supporting 4 times the suspended load of the unit you are using. If it cannot, the ceiling **MUST** be reinforced.

INSTALLATION INSTRUCTIONS

1. Turn projector upside down.
2. Place the LCD-7000 Plate onto the projector bottom so the (3) thru holes line up with the thread inserts in the bottom of projector. Using the M5 bolts and M5 washers, attach plate to the projector at these three places.
3. Attach the LCD-7000 U-Form around the projector and up through the two holes in the LCD-7000 plate, secure firmly using the #10 flat washers and 10-24 nylock nuts. **NOTE: This U-Form rod MUST be attached for mount to properly support projector. Felt squares are provided to protect projector shell, if desired. They can be attached to the projector or wrapped around the U-Form rod.**
4. Attach the LCD-7000 top cross assembly to the LCD-7000 plate installing it over the (4) thread studs and then securing it with the (4) ¼-20 nylock nuts.
5. Install the LCD-7000CI mount to your method of ceiling support and tighten. Install the ⁵/₁₆-18 set screw into the threaded collar and tighten.

TO ADJUST YAW:

Loosen set screw (see 2) and turn collar to desired yaw; tighten set screw.

TO ADJUST PITCH:

Loosen the four allen head bolts (see 1) and adjust to desired pitch; tighten bolts.

8804-000059
12/10/03