














INSTALLATION INSTRUCTIONS



- Go to <https://www.milestone.com/~media/files/chief/manuals/MSPDCCPSMH1-WEB-I.pdf> for translated instructions.
- Entre en <https://www.milestone.com/~media/files/chief/manuals/MSPDCCPSMH1-WEB-I.pdf> para obtener las instrucciones traducidas en su idioma.
- Bedienungsanleitungen in Ihrer Sprache finden Sie auf <https://www.milestone.com/~media/files/chief/manuals/MSPDCCPSMH1-WEB-I.pdf>.
- Pour la traduction des instructions, allez à <https://www.milestone.com/~media/files/chief/manuals/MSPDCCPSMH1-WEB-I.pdf>.
- Visitare il sito <https://www.milestone.com/~media/files/chief/manuals/MSPDCCPSMH1-WEB-I.pdf> per le istruzioni tradotte.
- Visite <https://www.milestone.com/~media/files/chief/manuals/MSPDCCPSMH1-WEB-I.pdf> para obter instruções traduzidas.
- 日本語の説明書は、<https://www.milestone.com/~media/files/chief/manuals/MSPDCCPSMH1-WEB-I.pdf> をご覧ください。
- 访问 <https://www.milestone.com/~media/files/chief/manuals/MSPDCCPSMH1-WEB-I.pdf> 参考说明书译本。
- 如需翻譯版指示說明，請前往 <https://www.milestone.com/~media/files/chief/manuals/MSPDCCPSMH1-WEB-I.pdf>。
- 번역된 안내서를 보려면 <https://www.milestone.com/~media/files/chief/manuals/MSPDCCPSMH1-WEB-I.pdf> 을(를) 방문하십시오.
- โปรดเข้าไปที่ <https://www.milestone.com/~media/files/chief/manuals/MSPDCCPSMH1-WEB-I.pdf> สำหรับคำแนะนำฉบับแปล

Large Flat Panel Static Wall Mount

LEGEND

| | | | | | |
|---|-------------------------------|-------------------|---|---------------------------|--------------------|
|  | Tighten Fastener | |  | Pencil Mark | |
| | Apretar elemento de fijación | 留め具を締める | | Marcar con lápiz | 鉛筆で印を付ける |
| | Befestigungsteil festziehen | 上紧紧固件 | | Stiftmarkierung | 铅笔标记 |
| | Serrez les fixations | 旋緊扣件 | | Marquage au crayon | 鉛筆標記 |
| | Serrare il fissaggio | 페스너 조이기 | | Segno a matita | 연필 표시 |
| | Apertar fixador | ตั้งสายรัดให้แน่น | | Marcar com lápis | ดินสอทำเครื่องหมาย |
|  | Loosen Fastener | |  | Drill Hole | |
| | Aflojar elemento de fijación | 留め具を緩める | | Perforar | ドリルで穴を開ける |
| | Befestigungsteil lösen | 松开紧固件 | | Bohrloch | 钻孔 |
| | Desserrez les fixations | 鬆開扣件 | | Percez un trou | 鑽孔 |
| | Allentare il fissaggio | 페스너 풀기 | | Praticare un foro | 드릴 구멍 |
| | Soltar fixador | คลายสายรัดให้หลวม | | Perfurar | เจาะรู |
|  | Phillips Screwdriver | |  | Adjust | |
| | Destornillador Phillips | プラスドライバー | | Ajustar | 調節する |
| | Kreuzschlitzschraubendreher | 十字螺丝刀 | | Einstellen | 调节 |
| | Tournevis à pointe cruciforme | 十字螺絲起子 | | Ajuster | 調整 |
| | Cacciavite a stella | 십자 나사드라이버 | | Regolare | 조정 |
| | Chave de fendas Phillips | ไขควงปากแฉก | | Regular | ปรับ |
|  | Open-Ended Wrench | |  | Hex-Head Wrench | |
| | Llave de boca | スパナ | | Llave de cabeza hexagonal | 六角レンチ |
| | Gabelschlüssel | 开口扳手 | | Sechskantschlüssel | 六头扳手 |
| | Clé à fourche | 雙頭扳手 | | Clé à tête hexagonale | 六角扳手 |
| | Chiave a punta aperte | 양입 렌치 | | Chiave esagonale | 육각 렌치 |
| | Chave de porcas aberta | ประแจปากคายน | | Chave sextavada | ประแจหัวหกเหลี่ยม |
|  | By Hand | |  | Socket Wrench | |
| | A mano | 手で行う | | Llave de cubo | socket wrench |
| | Von Hand | 手动 | | Steckschlüssel | 套筒扳手 |
| | À la main | 以手操作 | | Clé à douilles | 套筒扳手 |
| | A mano | 손으로 | | Chiave a brugola | socket wrench |
| | À mão | ด้วยมือ | | Chave de tubos | ประแจกระบอก |
|  | Hammer | |  | Measure | |
| | Martillo | ハンマー | | Medir | メジャー |
| | Hammer | 锤子 | | Messen | 測量 |
| | Marteau | 鐵鎚 | | Mesurer | 測量 |
| | Martello | 망치 | | Misura | 줄자 |
| | Martelo | ค้อน | | Medir | วัด |

DISCLAIMER

Milestone AV Technologies and its affiliated corporations and subsidiaries (collectively "Milestone"), intend to make this manual accurate and complete. However, Milestone makes no claim that the information contained herein covers all details, conditions or variations, nor does it provide for every possible contingency in connection with the installation or use of this product. The information contained in this document is subject to change without notice or obligation of any kind. Milestone makes no representation of warranty, expressed or implied, regarding the information contained herein. Milestone assumes no responsibility for accuracy, completeness or sufficiency of the information contained in this document.

Chief® is a registered trademark of Milestone AV Technologies. All rights reserved.

DEFINITIONS

MOUNTING SYSTEM: A MOUNTING SYSTEM is the primary Chief product to which an accessory and/or component is attached.

ACCESSORY: AN ACCESSORY is the secondary Chief product which is attached to a primary Chief product, and may have a component attached or setting on it.

COMPONENT: A COMPONENT is an audiovisual item designed to be attached or resting on an accessory or mounting system such as a video camera, CPU, screen, display, projector, etc.



WARNING: A WARNING alerts you to the possibility of serious injury or death if you do not follow the instructions.



CAUTION: A CAUTION alerts you to the possibility of damage or destruction of equipment if you do not follow the corresponding instructions.



IMPORTANT SAFETY INSTRUCTIONS



WARNING: Failure to read, thoroughly understand, and follow all instructions can result in serious personal injury, damage to equipment, or voiding of factory warranty! It is the installer's responsibility to make sure all mounting systems are properly assembled and installed using the instructions provided.



WARNING: Failure to provide adequate structural strength for this mounting system can result in serious personal injury or damage to equipment! It is the installer's responsibility to make sure the structure to which this mounting system is attached can support a minimum of 2,000 lbs (907.2 kg). Reinforce the structure as required before installing the mounting system. The wall to which the mounting system is being attached may have a maximum drywall thickness of 5/8" (1.6cm). Do not install drywall anchors into the seam between drywall pieces.



WARNING: Exceeding the weight capacity can result in serious personal injury or damage to equipment! It is the installer's responsibility to make sure the structure to which this mounting system is attached can support a minimum of 2,000 lbs (907.2 kg). **Reinforce the structure as required before installing this mount.** It is the installer's responsibility to make sure the combined weight of all components attached to the mounting system does not exceed 500 lbs (226.8 kg).



WARNING: Use this mounting system only for its intended use as described in these instructions. Do not use attachments not recommended by the manufacturer.



WARNING: Never operate this mounting system if it is damaged. Return the mounting system to a service center for examination and repair.




WARNING: Do not use this mounting system outdoors.

IMPORTANT ! : The MSP-DCCPSMH1 mounting system is designed to be mounted to a:


- 2" x 4" wood studs (16" on center or 24" on center) wall.

--SAVE THESE INSTRUCTIONS--


DIMENSIONS



TOOLS REQUIRED FOR INSTALLATION



PARTS



Assembly and Installation

The MSP-DCCPSMH1 is designed to be installed on 2" x 4" wood studs, 16" on-center or 24" on-center.

Mount Assembly

IMPORTANT ! : Be sure that Q-latches on vertical brackets are located on **outside** edges of mount. (See Figure 1)

1. Attach two vertical brackets (B and C) to two horizontal brackets (A) using sixteen M8 x 16mm buttonhead cap screws (F). (See Figure 1)




Figure 1

Mount Installation



WARNING: IMPROPER INSTALLATION CAN LEAD TO DISPLAY FALLING CAUSING SERIOUS PERSONAL INJURY OR DAMAGE TO EQUIPMENT! It is the installer's responsibility to make sure the structure to which this mount is being attached can support a minimum of 2,000 lbs (907.2 kg). Reinforce the structure as required before installing this mount.

1. Place mount against wall in desired installation location.
2. Level and adjust horizontal position making certain slots in upper and lower horizontal brackets on mount are properly positioned over studs.
3. Using a pencil, or similar marking tool, mark the location of six mounting holes (or four mounting holes for 24" on-center studs) in horizontal brackets onto surface. (See Figure 2)
4. Drill six 7/32" (four for 24" on-center studs) pilot holes at marked locations.



CAUTION: IMPROPER INSTALLATION CAN LEAD TO MOUNT FALLING CAUSING SERIOUS PERSONAL INJURY OR DAMAGE TO EQUIPMENT! DO NOT over tighten hardware!

5. Secure mount to studs using six 5/16 x 2-1/2" lag screws (G) and six 5/16" (H) flat washers [or four lag screws and four washers for 24" on-center studs]. (See Figure 2)




Figure 2

Display Installation



WARNING: IMPROPER INSTALLATION CAN LEAD TO MOUNT FALLING CAUSING SERIOUS PERSONAL INJURY OR DAMAGE TO EQUIPMENT! DO NOT substitute hardware.

1. Move Q-Latches on mount to the **OPEN** position. (See Figure 3)




Figure 3

2. Install four mounting buttons (D) onto display using four M8 x 35mm button head screws (E). (See Figure 4)




Figure 4

3. Lift display following lifting instructions provided by display manufacturer.
4. Align mounting buttons on display with teardrop mounting holes in mount. (See Figure 5)
5. Move display forward until recessed area of mounting buttons is positioned over lower area of teardrop mounting holes. (See Figure 5)

6. Lower display until recess area of mounting buttons is seated in lower area of teardrop mounting holes. (See Figure 5)




Figure 5

7. Move Q-Latches to **CLOSED** position and lock. (See Figure 6)




Figure 6

8. Route wires and cables to display.



Our Mounts. **Your Vision.**

Chief, a products division of
Milestone AV Technologies

4N3FC
8800-002968 Rev00
©2017 Milestone AV Technologies
www.milestone.com
03/17

| | |
|--------------------------|--|
| USA/International | A 6436 City West Parkway, Eden Prairie, MN 55344 |
| | P 800.582.6480 / 952.225.6000 |
| | F 877.894.6918 / 952.894.6918 |
| Europe | A Franklinstraat 14, 6003 DK Weert, Netherlands |
| | P +31 (0) 495 580 852 |
| | F +31 (0) 495 580 845 |
| Asia Pacific | A Office No. 918 on 9/F, Shatin Galleria 18-24 Shan Mei Street Fotan, Shatin, Hong Kong |
| | P 852 2145 4099 |
| | F 852 2145 4477 |

