



INSTALLATION INSTRUCTIONS

PSB-2181 PLASMA DISPLAY MOUNTING BRACKET

Prior to assembly, unpack carton completely and verify contents.
If you are missing any of the following components, please contact Customer Service at 1-800/582-6480




Figure 1

- (1) Plasma Static Mount Bracket
- (4) Mounting Buttons
- (4) M5-.8 x 12 Button HCS

- (1) M3 Allen Key
- (4) 10-24 x .5 Button Head Cap Screws
- (1) 1/8" Allen Key

BEFORE PROCEEDING, READ INSTALLATION INSTRUCTIONS COMPLETELY

CAUTION! PLASMA DISPLAYS ARE EXTREMELY FRAGILE.

1. Using a 10-24 button head cap screw inserted from the back side of bracket, secure mounting button, to bracket (four places) (see Figure 2 & Figure 3).
2. Align hole pattern on brackets with pattern on back of Plasma Display and attach using the M5 button head cap screws (see Figure 4).
3. With the aid of another person, lift Plasma Display up to the Chief Mount, aligning buttons of mounting brackets with slots in the Chief Mount.
4. Lower safety catch on the Chief Mount to secure Plasma Display, making sure catch is completely engaged.




Figure 2




Figure 3




Figure 4