



INSTALLATION INSTRUCTIONS

PSB-2537

LARGE FLAT PANEL DISPLAY MOUNTING BRACKET

Prior to assembly, unpack carton completely and verify contents.

If you are missing any of the following components, please contact Customer Service at 1-800/582-6480




Figure 1




Figure 2




Figure 3




Figure 4

- (2) Plasma Side Bracket
- (4) Mounting Button - Tapped
- (4) .74 x .39 x 1.0 Nylon Spacer
- (1) M5 Allen Key
- (4) .75 x .344 x .50 Nylon Spacer

- (2) Plasma Top/Bottom Bracket
- (8) 10-24 x .5 Button Head Cap Screw
- (1) 1/8 Allen Key
- (4) M8 x 60mm Button Head Cap Screw

BEFORE PROCEEDING, READ INSTALLATION INSTRUCTIONS COMPLETELY

CAUTION! DISPLAYS ARE EXTREMELY FRAGILE.

1. Using a 10-24 button head cap screw inserted from back side of bracket, secure mounting button, with chamfered hole of mounting button (larger surface) facing bracket, to top and bottom brackets (four places) (see Figure 2 & Figure 3).
2. Using four 10-24 button head cap screws, attach top and bottom to side brackets (see Figure 4 & Figure 5).
3. Stack both spacers (.5" and 1") over mounting holes and attach to display using the M8 screws.
4. With the aid of another person, lift your display up to the Chief Mount, aligning buttons of mounting brackets with slots in the Chief Mount.
5. Lower safety latch on the Chief Mount to secure your display, making sure latch is completely engaged.




Figure 5




Figure 6




Figure 7