



INSTALLATION INSTRUCTIONS

SLB-860 HANGER BRACKET

for Hitachi CP-S860, CP-X960 3M 8670

Prior to assembly, unpack carton and verify contents.

For security installation, use security hardware package inside the ALL-POINTS™ Security Kit. Follow the instructions below for attaching the bracket to the projector using either standard hardware or security hardware.

If you are missing any of the following components, please contact Customer Service at 1-800-582-6480

- | | | | |
|-----|--------------------------|-----|-------------------|
| (1) | SLB-860 Bracket Fig. # 1 | (4) | Thumb Nuts |
| (1) | U-Form Bracket Fig. # 2 | (2) | #10 Flatwashers |
| (4) | Felt Squares (1"x 1") | (2) | 10x24 Nylock Nuts |
| (3) | M4 x 10mm Screws | (3) | #4 Flatwashers |




Fig. # 1



Fig. # 2

INSTALLATION INSTRUCTIONS

1. Turn projector upside down.
2. Raise the front adjustable feet and Place SLB-860 bracket on the projector so the front slots in the bracket are around the adjustable feet and the two front mounting holes in the bracket line up with the two mounting inserts in the bottom front of the projector. (Note only three holes will line-up.)
3. Attach the SLB-860 bracket using the three 4 x 10mm mounting screws and # 4 washers. Tighten the two front adjustable feet against the projector.
4. Attach the U-Form bracket around the projector and up through the holes in the SLB-860 bracket, secure the U-Form using the two #10 flatwashers and 10-24 nylock nuts. **CAUTION: When attaching the U-Form bracket it should be left loose to the projector, it may affect operation of your projector and damage will occur if nuts are over tightened. When attaching the mount be careful not to overtighten the mounting screws. NOTE: Felt squares are provided to protect projector shell, if desired. They can be attached to the projector or wrapped around the U-Form rod.**
3. See RPA/Smart-Lift™ Instructions.

