



SMA-650 INSTALLATION ADAPTER KIT FOR THE SMART-LIFT 236

The SMA-650 installation adapter kit allows you to attach the Smart-Lift (model SL-236) to threaded rods or cables for suspended ceiling mounting applications.

Unpack carton and check contents:

- | | | | |
|-----|-----------------------------|-----|-------------------------------|
| (2) | Adapter, hanging rod | (4) | Nut, Nylock, 3/8-16 |
| (4) | Bolt, hex head, 3/8-16 X 1" | (8) | Washer, 0.375 X 0.906 X 0.083 |

CAUTION!!! The overhead support must be capable of supporting five times the combined weight of the lift and all equipment. If it cannot, it MUST be reinforced.

INSTALLATION INSTRUCTIONS

1. Open Smart-Lift (refer to Smart-Lift Instructions).
2. From the inside of the Smart Lift, insert four hex head bolts with washers into the holes in the top of the Smart Lift.
3. Place two hanging rod adapters over the bolts inserted in the top of the Smart Lift. Make sure any cover mounting bolts line up with the cutouts in the hanging rod adapters as necessary (see Figure 1).
4. Secure two hanging rod adapters to the Smart Lift using four Nylock nuts and washers.
5. See *Smart-Lift installation instructions* for proper installation procedures.

